TRADE PRESS RELEASE

MEDIA INQUIRIES

New Product Introduction

Caterpillar Trade Press Media Representative Johanna Kelly: Kelly Johanna L@cat.com

Versatile new Cat® Tiltrotators deliver fully integrated solution to increase machine utilization and help lower costs

- Multi-function capability allows for simultaneous 360° rotation and up to 40° left and right tilt
- High-flow hydraulic performance up to 200 l/min (52 gpm)
- o One grease point connection with the machine's auto-grease system

MUNICH, Germany, April 7, 2025 – Delivering all-round performance, the new Cat® Tiltrotator line helps to deliver significant cost savings by reducing the number of machines and ground staff at the site. The tilt rotate system allows the attachment to simultaneously rotate 360° and tilt up to 40°, allowing tracked excavators to perform a range of tasks – digging, grading and compacting – with more precise movements without repositioning the machine. Less machine repositioning helps to reduce undercarriage wear and lower costs.

"Our fully integrated new TRS12, TRS17, TRS20, and TRS26 models reduce installation time and show up automatically on the machine's monitor, allowing it to be easily controlled by the joystick," says Scott Rosengaard, senior product consultant for Caterpillar. "Our tiltrotators can be used with a wide range of attachments like buckets, grapples, compactors and more, allowing for higher machine utilization and improved productivity. Plus, the new standard tilt sensor delivers precise tilt and rotation angles to the grading system."

High-flow system

These new models feature a standard high flow swivel, providing up to 200 l/min flow at 250 bar (52 gpm at 3,626 psi) for use with high-flow work tools. Pairing the tiltrotator with a next generation Cat excavator that has a second hydraulic line boosts hydraulic flow and pressure to 250 l/min at 350 bar (66 gpm at 5,076 psi).

New pressure compensated hydraulic valves manufactured with spools provide even better control of the hydraulic flow than previous designs, allowing the tiltrotator to maintain stable rotation speed regardless of tilt speed. A quick-connect interface provides fast hydraulic attachment changes. SecureLock™ uses sensor technology inside the locking cylinder to verify the tool is correctly connected and securely locked to reduce the risk of swinging or dropping tools.

High efficiency

Cat TRS models feature a single grease point connection with the excavator's auto-grease system, and the



TRADE PRESS RELEASE

New Product Introduction

simple-to-use innovative lubrication system is developed to quickly distribute the right amount of grease to the appropriate points. Double-acting tilt cylinders fitted with a load holding valve ensure the load is securely in position, even in the event of the hydraulic system losing pressure. Providing maximum heat distribution, the worm gearbox is filled with oil for optimum lubrication.

With the new tiltrotator models, operators can change tools without leaving the cab when equipped with the full hydraulic coupler, enhancing safety, productivity, performance, and efficiency.

A plastic cover with built-in electrical harness provides easy connection to the hydraulic valves and simplifies servicing. Frame modification on the new series reduces dirt exposure for the grading sensor, which is further protected by a metal cover.

A complete list of Cat Tiltrotators available by region can be found by visiting a cat dealer or cat.com.

TILTROTATOR SPECIFICATIONS

| Model | Recommended Carrier Weight | | Weight | | Maximum Bucket | |
|-------|----------------------------|-------------|---------|-------|----------------|----|
| | Minimum | Maximum | vveigni | | Width | |
| | tons (lb) | tons (lb) | kg | lb | mm | in |
| TRS12 | 12 (26,455) | 16 (35,274) | 513 | 1,131 | 1600 | 63 |
| TRS17 | 14 (30,864) | 19 (41,887) | 644 | 1,420 | 1700 | 68 |
| TRS20 | 18 (39,683) | 24 (52,910) | 755 | 1,664 | 1800 | 71 |
| TRS26 | 23 (50,706) | 32 (70,584) | 938 | 2,068 | 2000 | 79 |

####



TRADE PRESS RELEASE

New Product Introduction

NOTE TO EDITORS

About Caterpillar:

With 2024 sales and revenues of \$64.8 billion, Caterpillar Inc. is the world's leading manufacturer of construction and mining equipment, off-highway diesel and natural gas engines, industrial gas turbines and diesel-electric locomotives. For 100 years, we've been helping customers build a better, more sustainable world and are committed and contributing to a reduced-carbon future. Our innovative products and services, backed by our global dealer network, provide exceptional value that helps customers succeed. Caterpillar does business on every continent, principally operating through three primary segments – Construction Industries, Resource Industries and Energy & Transportation – and providing financing and related services through our Financial Products segment. Visit us at caterpillar.com or join the conversation on our social media channels at caterpillar.com/en/news/social-media.html.

Caterpillar rolls out products and services in each of its regions at different time intervals. Although every effort is made to ensure that product information is released only after Caterpillar has received confirmation from its independent dealer network, plants, and marketing subsidiaries that products and services are available in the relevant region, editors are kindly requested to verify with a Cat dealer for product availability and specifications.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Caterpillar Inc., registered in the United States and in other countries.

Release Number: 68PR25 — April 2025

For Release: North America, South America, Europe

